



# VT-FORS GOLD FLATBED VAN

Bespoke kit designed specifically for flatbed vans and +3.5 tonne vehicles.

## THIS KIT INCLUDES THE FOLLOWING:

1. **VT5500-G-1TB**  
5CH MDVR  
Includes 1TB Hard-drive



2. **VT-C20-MINI\*\***  
Forward-facing Camera



3. **VT-LT ALERT**  
Left-turn Alert



4. **VT-CAN-M8\***  
Side Scan Interface  
(Vehicle 2012 or newer)



5. **VT-WNREVERSINGALARM**  
White Noise  
Reversing Alarm



6. **VT-TIMER CUT OUT**  
Timer cut-out button



7. **VT-M4-7-AHD (Kit)**  
4CH AHD Monitor  
Includes 5M Cable, F2F Convertor, Brackets



8. **VT408-AHD x2**  
HD Side-View Camera



9. **VT408 Spacer 50mm x2**  
**VT408 Spacer 25mm x2**



10. **VT-SIDE SCAN**  
VT-Sensor Brain (No Sensors)  
VT-Sensor Display + Mixture of x4 sensors



11. **VT646-AHD\*\*\***  
Rear-view  
Camera



12. **VT-C5M x3**  
5 Metre Cable



13. **VT-C15M**  
15 Metre Cable



14. **VT-WARNING STICKER**  
**BLIND SPOT**  
Warning Sticker



Product specifications can be found on the next page of this documents. \* additional charge may be involved. \*\*Not required for FORS but VisionTrack recommend. \*\*\*FORS require for 7.5 tonne vehicles but VisionTrack recommend for 3.5 and 7.5 tonne



### KEY FEATURES:

#### VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS, Wi-Fi and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design



#### VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable – IP6



#### VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



#### VT408-AHD

- DC 12V~24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- 20°C + 70°C
- 1280 x 720 pixels



#### VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage



#### VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- 3.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm



#### VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable – IP67
- 2 Wire



#### VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V~36V
- 352(L) x 166(W) x 32(D) mm



#### VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



#### VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



#### VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle)
- IR night vision
- 50(L) x 50(H) x 80(W)mm



#### VT-WARNING STICKER BLIND SPOT



For more information please go to [www.visiontrack.com](http://www.visiontrack.com)

