

VT-FORS GOLD PANEL VAN

GOLD



VT-FORS GOLD PANEL VAN

Bespoke kit designed specifically for panel vans.

THIS KIT INCLUDES THE FOLLOWING:

- 1. VT5500-G-1TB 5CH MDVR Includes 1TB Hard-drive
- 4. VT-CAN-M8 Side Scan Interface (Vehicle 2012 or newer)
- 7. VT-MM-AHD (Kit) 3CH AHD Monitor Includes 5M Cable, F2F Convertor, Brackets
- 10. VT-SIDE SCAN VT-Sensor Brain (No Sensors) VT-Sensor Display + Mixture of x4 sensors

2. VT-C20-MINI** Forward-facing Camera



- 5. VT-WNREVERSINGALARM** White Noise Reversing Alarm
- 8. VT408-AHD x2 HD Side-View Camera



6. VT-TIMER CUT OUT Timer cut-out button

3. VT-LT ALERT

Left-turn

Alert



9. VT408 Spacer 50mm x2 VT408 Spacer 25mm x2



11. **VT670-FHD***** Rear-view Camera



0

ST 8288 87 111

12. VT-C5M x 3 VT-C15M x 1 5 and 15 Metre Cables



13. VT-WARNING STICKER BLIND SPOT

Vehicle Signage



Product specifications can be found on the next page of this documents. *additional charge may be involved. **Not required for FORS but VisionTrack recommend. ***FORS recommend for 7.5 tonne vehicles, VisionTrack recommend for 3.5 and 7.5 tonne.

www.visiontrack.com

& 01246 225 745

🔀 info@visiontrack.com

VisionTrack Copyright © 2020 - All Rights Reserved. *All manufacturers specifications are subject to change without notice. No liability will be accepted by VisionTrack for any errors or omissions in this information.

VT-FORS GOLD PANEL VAN

KEY FEATURES:

VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS, Wi-Fi and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design

VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable IP6

VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- **12-14**V
- IP67 rated sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm

VT408-AHD

- DC 12V~24V
- **120°**
- 62(L) x 44(H) x 62(W) (mm)
- -20ºC + 70ºC
- 1280 x 720 pixels

VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage

VT-WARNING STICKER BLIND SPOT



For more information please go to www.visiontrack.com

www.visiontrack.com

VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- **3**.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm

VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable IP67
- 🗕 2 Wire

VT-MM-AHD (Kit)

- 7-inch digital screen
- 1280x720 resolution
- Remote control + keystoke
- Three video inputs, AV2/AV3 with trigger wire
- 248(L) x 106(H) x 27(D) (mm)

VT408 Spacer 50mm

■ 65(L) x 50(H) x 55(W) (mm)

VT408 Spacer 25mm

65(L) x 25(H) x 55(W) (mm)

VT670-AHD

- DC 12V
- **1**50°
- 198(L) x 28(H) x 27(D) (mm)
- Temp: -20ºC + 70ºC
- 640 x 480 Pixels



& 01246 225 745

🔀 info@visiontrack.com

VisionTrack Copyright © 2020 - All Rights Reserved. *All manufacturers specifications are subject to change without notice. No liability will be accepted by VisionTrack for any errors or omissions in this information.





NATING FORMER ETC











