VISIONTRACK





Blind spot Take care **⊙**VISIO∩TRACK





VT-FORS SILVER FLATBED VAN

Bespoke kit bit specifically for flatbed van vehicle types.

THIS KIT INCLUDES THE FOLLOWING:

1. VT-SIDE SCAN VT-Sensor Brain (No Sensors) VT-Sensor Display + Mixture of x4 sensors



2. VT-LT ALERT Left-turn Alert



3. VT-CAN-M8* Side Scan Interface (Vehicle 2012 or newer)



4. VT-WNREVERSINGALARM White Noise Reversing Alarm



5. VT-TIMER CUT OUT Timer cut-out button



6. VT-MM-AHD (Kit) 3CH AHD Monitor



7. VT408-AHD HD Side-View Camera



8. VT408 Spacer 50mm x1 VT408 Spacer 25mm x1



9. VT646-AHD** Rear-view Camera



10. VT-C10M 10 Metre Cable



11. VT-WARNING STICKER **BLIND SPOT** Vehicle Signage



Product specifications can be found on the next page of this documents. * additional charge may be involved.

**FORS require for over 7.5 tonne vehicles but VisionTrack Recommend for 3.5 and 7.5 tonne.









VISIONTRACK

KEY FEATURES:

VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage

VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable IP67
- 2 Wire

VT-MM-AHD (Kit)

- 7-inch digital screen
- 1280x720 resolution
- Remote control + keystoke
- Three video inputs, AV2/AV3 with trigger wire
- 248(L) x 106(H) x 27(D) (mm)

VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle)
- IR night vision
- 50(L) x 50(H) x 80(W)mm

VT-WARNING STICKER BLIND SPOT



For more information please go to www.visiontrack.com

VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable IP6

VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm

VT408-AHD

- DC 12V~24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- -20°C + 70°C
- 1280 x 720 pixels

VT408 Spacer 50mm

■ 65(L) x 50(H) x 55(W) (mm)

VT408 Spacer 25mm

■ 65(L) x 25(H) x 55(W) (mm)























